

**T-1 ISDN/PRI Line Configuration Options for  
Pika Priment MM 24, 48 or 96 port cards**

**Network Protocol = ISDN**

Options:

---

1. Framing:           a. T1 SF/D4       \_\_\_\_\_
- b. T1 ESF         \_\_\_\_\_
- 
2. Encoding:           a. T1 AMI         \_\_\_\_\_
- b. T1 B8ZS        \_\_\_\_\_
- 
3. Line Build-out:    a. 0 db            \_\_\_\_\_
- b. -7.5 db         \_\_\_\_\_
- c. -15.0 db        \_\_\_\_\_
- d. -22.5 db        \_\_\_\_\_
- e. 0-110 ft        \_\_\_\_\_
- f. 110-220 ft     \_\_\_\_\_
- g. 220-330 ft     \_\_\_\_\_
- h. 330-440 ft     \_\_\_\_\_
- i. 440-550 ft     \_\_\_\_\_
- j. 550-660 ft     \_\_\_\_\_
- 
4. Network Type:     a. Proprietary switch   \_\_\_\_\_
- b. National ISDN-1    \_\_\_\_\_
- c. National ISDN-2    \_\_\_\_\_
- 
5. Termination type: a. Client            \_\_\_\_\_
- b. Network            \_\_\_\_\_
- 
6. Network switch type: a. AT&T 4ESS         \_\_\_\_\_
- b. AT&T 5ESS         \_\_\_\_\_
- c. NorTel DMS-100    \_\_\_\_\_

7. Addressing type:           a. None                   \_\_\_\_\_
- b. International        \_\_\_\_\_
- c. National             \_\_\_\_\_
- d. Network specific    \_\_\_\_\_
- e. Local                 \_\_\_\_\_
- f. Subaddress           \_\_\_\_\_
- g. Abbreviated         \_\_\_\_\_
- h. Continuation of address \_\_\_\_\_
8. CODEC compand mode:   a. A-Law                \_\_\_\_\_
- b. Mu-Law             \_\_\_\_\_ (North America)
9. Numbering plan:         a. None                 \_\_\_\_\_
- b. ISDN (E.164)        \_\_\_\_\_
- c. Private              \_\_\_\_\_
10. Bearer capabilities:    a. Speech               X   (Do not change)
11. Transfer rate:         a. 56Kbps             \_\_\_\_\_
- b. 64Kbps             \_\_\_\_\_
12. Call Model Mode:      a. Normal               X   (Do not change)
- b. Automatic         \_\_\_\_\_

NXi Communications, Inc.  
 4505 S. Wasatch Blvd., Ste. 120  
 Salt Lake City, UT 84124  
 Ph: (801) 274-6001/Fax: (801) 274-6002  
 E-mail: nxi@nxicom.com