



Section 508 Accessibility Compliance Documentation
 Network Telephony Systems (NTS) / Call Center Solutions (CCS) Client

NXi Accessibility Statement and Responses to the Voluntary Product Accessibility Template

We continually strive to ensure the pages on this Web site are accessible to individuals with disabilities in accordance with [Section 508 of the Rehabilitation Act](#). If you have any difficulty viewing any page with adaptive technology, please contact the webmaster for this site, or the [Center Section 508 Coordinator](#).

Documents on the NXi Web site are presented in many formats. These formats are generally accessible to users using screen reading software. Some files on this Web site may be posted as Adobe Acrobat Portable Document Format (PDF) files. Adobe provides their [Acrobat Reader](#) software as a free download.

Date: February 23, 2006
 Name of Product(s): NXi Communications' Network Telephony Systems 6 (NTS 6) Client Software,
 NXi Communications' Call Center Solutions 6 (CCS 6) Client Software
 Contact for more Information: Glen Lowry (801) 453-2121 glen@nextalk.com

The NTS 6 and CCS 6 Client software is a PC-based client application which provides textual communications between TTYs and other TDD devices and the PC client. There is no audio component to the client and all textual functions of the client are certified to be Section 508 compliant.

Summary Table Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
Section 1194.21 Software Applications and Operating Systems		
Section 1194.22 Web-based internet information and applications		
Section 1194.23 Telecommunications Products		
Section 1194.24 Video and Multi-media Products		
Section 1194.25 Self-Contained, Closed Products		
Section 1194.26 Desktop and Portable Computers		
Section 1194.31 Functional Performance Criteria		

[top](#)

<http://www.itic.org/policy/VPT.html>

Section 1194.21 Software Applications and Operating Systems - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) When software is designed to run on a system that has a keyboard, product functions shall be executable from a keyboard where the function itself or the result of performing a function can be discerned textually.	Fully conforms to and uses the Microsoft keyboard accessibility standards	* NXi is a certified member of the Microsoft MATvp accessibility program
(b) Applications shall not disrupt or disable activated features of other products that are identified as accessibility features, where those features are developed and documented according to industry standards. Applications also shall not disrupt or disable activated features of any operating system that are identified as accessibility features where the application programming interface for those accessibility features has been documented by the manufacturer of the operating system and is available to the product developer.	Fully compliant	
(c) A well-defined on-screen indication of the current focus shall be provided that moves among interactive interface elements as the input focus changes. The focus shall be programmatically exposed so that Assistive Technology can track focus and focus changes.	Fully compliant	
(d) Sufficient information about a user interface element including the identity, operation and state of the element shall be available to Assistive Technology. When an image represents a program element, the information conveyed by the image must also be available in text.	Fully compliant	
(e) When bitmap images are used to identify controls, status indicators, or other programmatic elements, the meaning assigned to those images shall be consistent throughout an application's performance.	Fully compliant	
(f) Textual information shall be provided through operating system functions for displaying text. The minimum information that shall be made available is text content, text input caret location, and text attributes.	Fully compliant	
(g) Applications shall not override user selected contrast and color selections and other individual display attributes.	Fully compliant	
(h) When animation is displayed, the	Not applicable	

information shall be displayable in at least one non-animated presentation mode at the option of the user.		
(i) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Fully compliant	Application uses icons, textual responses and menus. Color schemes are modifyable by the user.
(j) When a product permits a user to adjust color and contrast settings, a variety of color selections capable of producing a range of contrast levels shall be provided.	Fully compliant	See (i) above
(k) Software shall not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.	Fully compliant	Software supports industry standard interfaces for visual notifications
(l) When electronic forms are used, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.	Fully compliant	Includes support for leading screen readers or Braille devices

[top](#)

<http://www.itic.org/policy/VPT.html>

Section 1194.22 Web-based Internet information and applications - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) A text equivalent for every non-text element shall be provided (e.g., via "alt", "longdesc", or in element content).	Not applicable	Not web-based
(b) Equivalent alternatives for any multimedia presentation shall be synchronized with the presentation.	Not applicable	Not web-based
(c) Web pages shall be designed so that all information conveyed with color is also available without color, for example from context or markup.	Not applicable	Not web-based
(d) Documents shall be organized so they are readable without requiring an associated style sheet.	Not applicable	Not web-based
(e) Redundant text links shall be provided for	Not applicable	Not web-based

each active region of a server-side image map.		
(f) Client-side image maps shall be provided instead of server-side image maps except where the regions cannot be defined with an available geometric shape.	Not applicable	Not web-based
(g) Row and column headers shall be identified for data tables.	Not applicable	Not web-based
(h) Markup shall be used to associate data cells and header cells for data tables that have two or more logical levels of row or column headers.	Not applicable	Not web-based
(i) Frames shall be titled with text that facilitates frame identification and navigation	Not applicable	Not web-based
(j) Pages shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	Not web-based
(k) A text-only page, with equivalent information or functionality, shall be provided to make a web site comply with the provisions of this part, when compliance cannot be accomplished in any other way. The content of the text-only page shall be updated whenever the primary page changes.	Not applicable	Not web-based
(l) When pages utilize scripting languages to display content, or to create interface elements, the information provided by the script shall be identified with functional text that can be read by Assistive Technology.	Not applicable	Not web-based
(m) When a web page requires that an applet, plug-in or other application be present on the client system to interpret page content, the page must provide a link to a plug-in or applet that complies with 1194.21(a) through (l).	Not applicable	Not web-based
(n) When electronic forms are designed to be completed on-line, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.	Not applicable	Not web-based
(o) A method shall be provided that permits users to skip repetitive navigation links.	Not applicable	Not web-based
(p) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Not applicable	Not web-based

Note to 1194.22: The Board interprets paragraphs (a) through (k) of this section as consistent with the following priority 1 Checkpoints of the Web Content Accessibility Guidelines 1.0 (WCAG 1.0) (May 5 1999) published by the Web Accessibility Initiative of the World Wide Web Consortium: Paragraph (a) - 1.1, (b) - 1.4, (c) - 2.1, (d) - 6.1, (e) - 1.2, (f) - 9.1, (g) - 5.1, (h) - 5.2, (i) - 12.1, (j) - 7.1, (k) - 11.4.

[top](#)

<http://www.itic.org/policy/VPT.html>

Section 1194.23 Telecommunications Products - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) Telecommunications products or systems which provide a function allowing voice communication and which do not themselves provide a TTY functionality shall provide a standard non-acoustic connection point for TTYs. Microphones shall be capable of being turned on and off to allow the user to intermix speech with TTY use.	Clients do NOT allow voice communications	TTY to TTY functionality only
(b) Telecommunications products which include voice communication functionality shall support all commonly used cross-manufacturer non-proprietary standard TTY signal protocols.	Clients do NOT include voice communications	TTY to TTY functionality only
(c) Voice mail, auto-attendant, and interactive voice response telecommunications systems shall be usable by TTY users with their TTYs.	TTY mail, auto-attendant, and interactive text response are included in the client software.	TTY to TTY functionality only
(d) Voice mail, messaging, auto-attendant, and interactive voice response telecommunications systems that require a response from a user within a time interval, shall give an alert when the time interval is about to run out, and shall provide sufficient time for the user to indicate more time is required.	Delay time can be set by system administrator using an interactive script.	
(e) Where provided, caller identification and similar telecommunications functions shall also be available for users of TTYs, and for users who cannot see displays.	When using a T1 interface and ANI is provided, the ANI is passed to Call Center Agent clients and displayed on NTS client window.	
(f) For transmitted voice signals, telecommunications products shall provide a gain adjustable up to a minimum of 20 dB. For incremental volume control, at least one intermediate step of 12 dB of gain shall be provided.	Not applicable	TTY to TTY functionality only
(g) If the telecommunications product allows a user to adjust the receive volume, a function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	TTY to TTY functionality only

(h) Where a telecommunications product delivers output by an audio transducer which is normally held up to the ear, a means for effective magnetic wireless coupling to hearing technologies shall be provided.	Not applicable	TTY to TTY functionality only
(i) Interference to hearing technologies (including hearing aids, cochlear implants, and assistive listening devices) shall be reduced to the lowest possible level that allows a user of hearing technologies to utilize the telecommunications product.	Not applicable	TTY to TTY functionality only
(j) Products that transmit or conduct information or communication, shall pass through cross-manufacturer, non-proprietary, industry-standard codes, translation protocols, formats or other information necessary to provide the information or communication in a usable format. Technologies which use encoding, signal compression, format transformation, or similar techniques shall not remove information needed for access or shall restore it upon delivery.	All communications external to the IP connection are TTY to TTY compatible.	TTY to TTY functionality only
(k)(1) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be tactilely discernible without activating the controls or keys.	Not applicable	Standard keyboard interface
(k)(2) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be operable with one hand and shall not require tight grasping, pinching, twisting of the wrist. The force required to activate controls and keys shall be 5 lbs. (22.2N) maximum.	Not applicable	Standard keyboard interface
(k)(3) Products which have mechanically operated controls or keys shall comply with the following: If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character.	Not applicable	Standard keyboard interface
(k)(4) Products which have mechanically operated controls or keys shall comply with the following: The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound.	Not applicable	Standard keyboard interface

[top](#)

Section 1194.24 Video and Multi-media Products - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
a) All analog television displays 13 inches and larger, and computer equipment that includes analog television receiver or display circuitry, shall be equipped with caption decoder circuitry which appropriately receives, decodes, and displays closed captions from broadcast, cable, videotape, and DVD signals. As soon as practicable, but not later than July 1, 2002, widescreen digital television (DTV) displays measuring at least 7.8 inches vertically, DTV sets with conventional displays measuring at least 13 inches vertically, and stand-alone DTV tuners, whether or not they are marketed with display screens, and computer equipment that includes DTV receiver or display circuitry, shall be equipped with caption decoder circuitry which appropriately receives, decodes, and displays closed captions from broadcast, cable, videotape, and DVD signals.	Not applicable	TTY to TTY compatibility only
(b) Television tuners, including tuner cards for use in computers, shall be equipped with secondary audio program playback circuitry.	Not applicable	TTY to TTY functionality only
(c) All training and informational video and multimedia productions which support the agency's mission, regardless of format, that contain speech or other audio information necessary for the comprehension of the content, shall be open or closed captioned.	Not applicable	TTY to TTY functionality only
(d) All training and informational video and multimedia productions which support the agency's mission, regardless of format, that contain visual information necessary for the comprehension of the content, shall be audio described.	Not applicable	TTY to TTY functionality only
(e) Display or presentation of alternate text presentation or audio descriptions shall be user-selectable unless permanent.	Not applicable	TTY to TTY functionality only

[top](#)

Voluntary Product Accessibility Template

Criteria	Supporting Features	Remarks and explanations
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Not applicable	
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Not applicable	
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	Not applicable	
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable	
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Not applicable	
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls	Not applicable	

shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.		
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	Not applicable	
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	Not applicable	
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	Not applicable	

[top](#)

<http://www.itic.org/policy/VPT.html>

Section 1194.26 Desktop and Portable Computers - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) All mechanically operated controls and keys shall comply with 1194.23 (k) (1) through (4).	Not applicable	
(b) If a product utilizes touchscreens or touch-operated controls, an input method shall be provided that complies with 1194.23 (k) (1) through (4).	Not applicable	
(c) When biometric forms of user identification or control are used, an alternative form of identification or	Not applicable	

activation, which does not require the user to possess particular biological characteristics, shall also be provided.		
(d) Where provided, at least one of each type of expansion slots, ports and connectors shall comply with publicly available industry standards	Not applicable	

[top](#)

<http://www.itic.org/policy/VPT.html>

Section 1194.31 Functional Performance Criteria - Detail Voluntary Product Accessibility Template		
Criteria	Supporting Features	Remarks and explanations
(a) At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for Assistive Technology used by people who are blind or visually impaired shall be provided.	Additional tools can be configured for people who are blind or visually impaired	
(b) At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged print output working together or independently, or support for Assistive Technology used by people who are visually impaired shall be provided.	Additional tools can be configured for people who are blind or visually impaired	
(c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided	The product provides textual communications for deaf and hearing impaired.	
(d) Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided.	Not applicable	
(e) At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided.	Not applicable	
(f) At least one mode of operation and information retrieval that does not require fine motor control or simultaneous actions and that is operable with limited reach and	All standard input/ accessibility interfaces are supported	

strength shall be provided.		
-----------------------------	--	--

[top](#)

Responsible NXi Officer: Thomas McLaughlin, President tom.m@nextalk.com
Date: February 23, 2006